

Application No. 09/646,790
Amendment
Response to Office Action dated April 29, 2004

Docket No. 200-19

AMENDMENTS TO THE CLAIMS

1-8. (Cancelled)

1 9. (Currently amended) An inkjet printer for printing on goods comprising:
2 a computer for controlling an operational process of the printer;
3 at least one exchangeable reservoir bottle filled initially with a previously known
4 quantity of a fluid;
5 an intermediate container that is rechargeable with fluid from the reservoir bottle;
6 a suction pipe and a pump for recharging fluid from the reservoir bottle to the
7 intermediate container;
8 a sensor arrangement for detecting the quantity of fluid drawn from the reservoir
9 bottle to sense depletion of fluid in the reservoir bottles;
10 an externally visible label provided on the reservoir bottle which carries coded
11 information about the fluid contained in the reservoir bottle;
12 means for feeding the label information into the computer when the reservoir bottle is
13 inserted into the printer; and
14 a test program provided in the computer that checks the label information and that
15 only allows normal operation of the inkjet printer when at least one selected test criterion is
16 acceptable;
17 wherein an output signal of the sensor arrangement for detecting the quantity of fluid
18 drawn from the reservoir bottle is fed into the computer and the computer compares the quantity of
19 fluid drawn from the reservoir bottle with the previously known quantity of fluid and emits a
20 "reservoir bottle empty" signal when the previously known quantity of fluid has been drawn from
21 the reservoir bottle indicating that the reservoir bottle is empty, the intermediate container being
22 however at least partially still full such that operation of the printer can continue to run during a
23 period of time sufficient to exchange a new reservoir bottle for the depleted reservoir bottle.

{WP203914.1}

Docket No. 200-19

Application No. 09/646,790

Amendment

Response to Office Action dated April 29, 2004

1 10. (Previously presented) The inkjet printer according to claim 9, wherein at the same
2 time as the computer emits the signal "reservoir bottle empty", the computer suspends the tapping
3 of fluid from the reservoir bottle and only allows the tapping of fluid from a new reservoir bottle
4 after information from a new coded label has been input, which new reservoir bottle is installed to
5 replace the now empty reservoir bottle.

1 11. (Previously presented) The inkjet printer according to claim 9, wherein the volume
2 of the reservoir bottle is greater than the volume of the intermediate container.

1 12. (Previously presented) The inkjet printer according to claim 11, wherein the volume
2 of the reservoir bottle is more than six times the volume of the intermediate container.

1 13. (Previously presented) The inkjet printer according to claim 11, wherein the volume
2 of the reservoir bottle is more than ten times the volume of the intermediate container.

1 14. (Previously presented) The inkjet printer according to claim 9, wherein the
2 computer has a time unit that produces an internal date and this internal date is compared with the
3 date indicated on the label.

1 15. (Previously presented) The inkjet printer according to claim 9, wherein the
2 computer is provided with a memory in which the information from the label is stored.

1 16. (Withdrawn) The inkjet printer according to claim 9, wherein the label
2 information is machine readable.

1 17. (Withdrawn) The inkjet printer according to claim 9, wherein the label
2 information is a bar code.

{WP203914.1}

5

Application No. 09/646,790
Amendment
Response to Office Action dated April 29, 2004

Docket No. 200-19

1 18. (Previously presented) The inkjet printer according to claim 9, wherein the label
2 information is one of the expiration date, the kind of fluid, the quantity of fluid and the viscosity of
3 fluid.

1 19. (Currently amended) The inkjet printer according to claim 9, wherein the
2 computer is provided with a memory in which the information from the label is stored and wherein
3 ~~means are provided to delete~~ the information stored in the memory is deleted when a new reservoir
4 bottle is inserted into the printer.

1 20. (Previously presented) The inkjet printer according to claim 9, wherein the least one
2 selected test criterion is the expiration date.

1 21. (Currently amended) An inkjet printer for printing on goods comprising in
2 combination:
3 a computer for controlling an operational process of the printer;
4 two exchangeable reservoir bottles, each reservoir bottle filled initially with a previously
5 known quantity of a fluid, the fluids in the two bottles being different;
6 an intermediate container that is recharged with fluid from at least one of the reservoir
7 bottles;
8 a suction pipe and a pump for recharging fluid from each one of the reservoir bottles to the
9 intermediate container;
10 a sensor arrangement for detecting the quantity of fluid drawn from each one of the
11 reservoir bottles to sense depletion of fluid in the reservoir bottles;
12 an externally visible label provided on each one of the reservoir bottles which carries coded
13 information about the fluid contained in the respective reservoir bottle;
14 means for feeding the label information into the computer when the reservoir bottles are
15 inserted into the printer; and
16 a test program provided in the computer that checks the input label information and that

{WP203914.1}

Application No. 09/646,790
Amendment
Response to Office Action dated April 29, 2004

Docket No. 200-19

17 only allows normal operation of the inkjet printer when at least one selected test criterion is
18 acceptable;
19 wherein an output signal of the sensor arrangement is fed into the computer and the
20 computer compares the quantity of fluid drawn from the reservoir bottle with the previously
21 known quantity of fluid and emits a "reservoir bottle empty" signal when the previously known
22 quantity of fluid has been drawn from one of the reservoir bottles indicating that the reservoir
23 bottle is empty, the intermediate container being however at least partially still full such that
24 operation of the printer can continue to run during a period of time sufficient to exchange a new
25 reservoir bottle for the depleted reservoir bottle.

1 22. (Previously presented) The inkjet printer according to claim 21, wherein one
2 reservoir bottle is filled with a solvent and the other reservoir bottle is filled with pigment.

1 23. (Withdrawn) The inkjet printer according to claim 21, wherein each reservoir
2 bottles are mechanically formed in different ways and wherein the insertion of a reservoir bottle at
3 a place assigned to another reservoir bottle with different fluid is mechanically hindered.